



HSM Pure 740 - 5.8 mm




HSM Pure 740 document shredder

The powerful shredder for the department. The sturdy and powerful cutting roller with a wide input width for paper up to DIN A3 impresses with its high cutting performance and low noise level in continuous operation.

Technical data

Order number:	2371811	Intake width:	400 mm
EAN	4026631054973	Container volume / collecting:	145 l
Cutting type:	strip cut	Noise level (idle operation):	ca. 56 dB(A)
Cutting width:	5,8 mm	Width x Depth x Height:	620 x 487 x 889 mm
Security level (DIN 66399):	E-2 O-2 P-2 T-2	Weight:	47,2 kg
Cutting capacity in sheets 80g/m²:	35 - 37	Shredder material:	Paper, Staples and paper clips, Credit card, CD/DVD
Power consumption:	590 W		
Voltage / Frequency:	230 V / 50 Hz		

Product information



The induction-hardened, solid steel cutting rollers with a lifetime warranty can easily cope with staples and paper clips and guarantee durability.



The document shredder has a sturdy cabinet with a wooden floor and an extra-large door opening angle which facilitates removing and replacing the collecting bag.



After opening the door, the removable, collecting bag can be easily removed and emptied.



For continuous operation

The powerful motor ensures a high cutting capacity and reliable continuous operation.



Energy-saving

The stand-by feature ensures a high degree of energy saving when the shredder is not in use.



Anti-paper jam function

The paper feed with overload protection reduces paper jams and sustains the high throughput of paper.



High level of user safety

User safety is paramount. A slight pressure on the safety element immediately stops the paper feed and prevents unintentional entry into the machine.



Automatic start/stop

The operation is very easy: the device starts automatically when fed with paper and automatically stops after shredding is complete.



Mobile on castors

For convenience, there are castors on the document shredder so it is easy to move around.



Lifetime warranty on solid steel cutting rollers at security levels P-2 to P-5 (according to ISO/IEC 21964).

