JBF DC + DCM 600 / 800 / 1000

Important Features

- Direct connection of power supply to terminals by customer's electrician
- Compliant with DIN 66399 security level P3 (DC + DCM 600) or P2 (DC + DCM 800 + 1000)
- Standard feed conveyor provides for convenient feeding of large amounts of documents
- Combination of a rugged primary shredder and a security shredder for creation of small particles
- DCM machines feature a magnetic separator for automatic separation of ferrous magnetic metals ahead the security shredder
- Handles thick computer printout lists and complete ring binders (suggested for DCM machines only)
- Processes up to approx. 600 / 800 / 1,000 kg paper documents per hour
- Handles small amounts of other data media like CD's, DVD's, floppy discs

Intended Range of Application

This machine was designed for operation directly in the administration of large companies or banks and for recyclers and shredding service providers. With its Siemens S7-1200 PLC with color touch panel it provides for automated destruction of large amounts of documents with only little human intervention. Installed on a trailer it can be used for ultra-high volume mobile shredding services.

Technical Data		DC / DCM 600	DC / DCM 800	DC / DCM 1000	
<u>Primary shredder:</u> Motor power	kW	7.5	9.2	2 x 7.5	
Working width	mm	380	380	380	
Knife width	mm	30	30	30	
<u>Secondary shredder:</u> Motor power	kW	9.2	887-* 101-201-201-201-201-201-201-201-201-201-		
			E00	Fag 1	
Working width	mm	500	500		
Knife width	mm	6 x 50 or 12 x 55	12 x 55	12 x 55	
Throughput capacity	kg/h	up to approx. 600	up to approx. 850	up to approx. 1,000	
<u>Complete machine:</u>				Section Section	
Power supply	V / Hz	400V / 50Hz / 3Phase (other voltages and frequencies available upon request)			
Machine weight	kg	up to approx. 5,260	upon request)		

Photo shows various optional equipment (tipping device, \dots)

ShreddingMachines.co.uk

Subject to change without prior notice All values are approximate



JBF DC + DCM 2000 / 2500

Important Features

- Direct connection of power supply to terminals by customer's electrician
- Compliant with DIN 66399 security level P2, levels P3 and P4 available as an option
- Standard feed conveyor provides for convenient feeding of large amounts of documents
- Combination of a rugged primary shredder and a security shredder for creation of small particles
- DCM machines feature a magnetic separator for automatic separation of ferrous magnetic metals ahead the security shredder
- Cutting shafts assembled from segments, which can be exchanged separately when damaged
- Handles thick computer printout lists and complete ring binders (suggested for DCM machines only)
- Processes up to approx. 2,000 / 3,200 kg paper documents per hour in level P2
- Handles other data media like CD´s, DVD´s, floppy discs
- A bypass allows to only pre-shred the material, activation within seconds via touch panel

Intended Range of Application

This machine was designed for operation directly in the administration of large companies or banks and for recyclers and shredding service providers. With its Siemens S7-1200 PLC with color touch panel it provides for automated destruction of large amounts of documents with only little human intervention. Installed on a trailer it can be used for ultra-high volume mobile shredding services.

Technical Data		DC / DCM 2000	DC / DCM 2500
<u>Primary shredder:</u> Motor power Working width Knife width	kW mm mm	2 x 9.2 700 40	2 x 15 700 40
<u>Secondary shredder:</u> Motor power Working width Knife width Throughput capacity	kW mm mm kg/h	2 x 9.2 730 12 x 55 up to approx. 2,100	2 x 11 880 12 x 55 up to 3,200
Complete machine: Power supplyV / HzMachine weightkg		400V / 50Hz / 3Phase (other voltages and frequencies available upon request) up to approx. 8,000	



ShreddingMachines.co.uk

Subject to change without prior notice All values are approximate

